

SHEET No.	DESCRIPTION
1	TITLE AND LOCATION MAP
2-6	CONSTRUCTION DETAILS
7-8	CONSTRUCTION AREA SIGNS
9-10	SUMMARY OF QUANTITIES
11-14	REVISED STANDARD PLANS

THE STANDARD PLANS LIST APPLICABLE TO THIS CONTRACT IS INCLUDED IN THE NOTICE TO BIDDERS AND SPECIAL PROVISIONS BOOK.

STATE OF CALIFORNIA
DEPARTMENT OF TRANSPORTATION


ACHSSTP-000C(439)

**PROJECT PLANS FOR CONSTRUCTION ON
 STATE HIGHWAY
 IN NEVADA COUNTY ON ROUTE 20 FROM NEVADA COUNTY
 LINE TO PENN VALLEY ROAD AND
 IN PLACER COUNTY ON ROUTE 267 FROM
 CARNELIAN BAY AVENUE TO ROUTE 28**

TO BE SUPPLEMENTED BY STANDARD PLANS DATED 2010


Dist	COUNTY	ROUTE	POST MILES TOTAL PROJECT	SHEET No.	TOTAL SHEETS
03	Nev, Pla	20,267	0.0/R6.6 6.8/9.9	1	14

LOCATION MAP



PROJECT MANAGER
SERGIO ACEVES
 DESIGN MANAGER
SCOTT W. MANN

PROJECT ENGINEER DATE 4-4-16
 REGISTERED CIVIL ENGINEER
April 4, 2016
 PLANS APPROVAL DATE
THE STATE OF CALIFORNIA OR ITS OFFICERS OR AGENTS SHALL NOT BE RESPONSIBLE FOR THE ACCURACY OR COMPLETENESS OF SCANNED COPIES OF THIS PLAN SHEET.



THE CONTRACTOR SHALL POSSESS THE CLASS (OR CLASSES) OF LICENSE AS SPECIFIED IN THE "NOTICE TO BIDDERS."

NO SCALE


CONTRACT No.	03-0H9904
PROJECT ID	0316000042

DATE PLOTTED => 17-MAY-2016
 TIME PLOTTED => 14:24
 00-00-00

Dist	COUNTY	ROUTE	POST MILES TOTAL PROJECT	SHEET No.	TOTAL SHEETS
03	NeV,Pla	20,267	0.0/R6.6 6.8/9.9	2	14
 REGISTERED CIVIL ENGINEER			4-4-16	DATE	
4-4-16 PLANS APPROVAL DATE					
<small>THE STATE OF CALIFORNIA OR ITS OFFICERS OR AGENTS SHALL NOT BE RESPONSIBLE FOR THE ACCURACY OR COMPLETENESS OF SCANNED COPIES OF THIS PLAN SHEET.</small>					

NOTES:

- EXISTING UTILITY FACILITIES HAVE NOT BEEN PLOTTED ON THESE PLANS.
- CENTERLINE RUMBLE STRIP SHALL BE CONSTRUCTED PRIOR TO INSTALLING THERMOPLASTIC TRAFFIC STRIPING.
- CENTERLINE STRIPING PATTERN TO MATCH EXISTING.
- SEE STANDARD PLAN A40B FOR SHOULDER RUMBLE STRIP DETAILS.
- SHOULDER RUMBLE STRIPS TO BE INSTALLED AT LOCATION 1 ONLY.




DETAIL 22 WITH CENTERLINE RUMBLE STRIPS (LOCATION 1)

REMOVE EXISTING STRIPING
REPLACE STRIPING IN THE SAME LOCATION
WITH 4" YELLOW THERMOPLASTIC STRIPE (EWNV)


LEGEND

-  DIRECTION OF TRAVEL
-  PAVEMENT MARKER (RETROREFLECTIVE), TYPE D, YELLOW
-  PAVEMENT MARKER (RETROREFLECTIVE), TYPE H, YELLOW
-  PAVEMENT MARKER (NON-REFLECTIVE), TYPE A, BLACK
-  CENTERLINE RUMBLE STRIP (HMA, GROUND-IN INDENTATIONS)
- EWNV ENHANCED WET NIGHT VISIBILITY




DETAIL 19 WITH CENTERLINE RUMBLE STRIPS (LOCATION 1)

REMOVE EXISTING STRIPING
REPLACE STRIPING IN THE SAME LOCATION
WITH 4" YELLOW THERMOPLASTIC STRIPE (EWNV)



CENTERLINE RUMBLE STRIP (HMA, GROUND-IN INDENTATIONS) DETAILS



DETAIL 6 WITH CENTERLINE RUMBLE STRIPS (LOCATION 1)

REMOVE EXISTING STRIPING
REPLACE STRIPING IN THE SAME LOCATION
WITH 4" YELLOW THERMOPLASTIC STRIPE (EWNV)

CENTERLINE RUMBLE STRIPS (HMA, GROUND-IN INDENTATIONS)

CONSTRUCTION DETAILS

NO SCALE

C-1


STATE OF CALIFORNIA - DEPARTMENT OF TRANSPORTATION
 DESIGN
 FUNCTIONAL SUPERVISOR: SCOTT W. MANN
 CALCULATED/DESIGNED BY: CHRISTOPHER BRADANICK
 CHECKED BY: RODOLFO AVILA
 REVISED BY: DATE
 REVISIONS:

Dist	COUNTY	ROUTE	POST MILES TOTAL PROJECT	SHEET No.	TOTAL SHEETS
03	Nev, Pla	20,267	0.0/R6.6 6.8/9.9	3	14


<i>Scott W. Mann</i> REGISTERED CIVIL ENGINEER	4-4-16 DATE
4-4-16 PLANS APPROVAL DATE	

REGISTERED PROFESSIONAL ENGINEER
SCOTT MANN
No. 72005
Exp. 6-30-16
CIVIL


THE STATE OF CALIFORNIA OR ITS OFFICERS OR AGENTS SHALL NOT BE RESPONSIBLE FOR THE ACCURACY OR COMPLETENESS OF SCANNED COPIES OF THIS PLAN SHEET.




DETAIL 21 WITH CENTERLINE RUMBLE STRIPS (LOCATION 2)



DETAIL 18 WITH CENTERLINE RUMBLE STRIPS (LOCATION 2)



CENTERLINE RUMBLE STRIP (HMA, GROUND-IN INDENTATIONS) DETAILS



DETAIL 5 WITH CENTERLINE RUMBLE STRIPS (LOCATION 2)

CONSTRUCTION DETAILS

NO SCALE

C-2


STATE OF CALIFORNIA - DEPARTMENT OF TRANSPORTATION
DESIGN
FUNCTIONAL SUPERVISOR SCOTT W. MANN
CALCULATED/DESIGNED BY CHECKED BY
CHRISTOPHER BRADANICK RODOLFO AVILA
REVISED BY DATE REVISED

Dist	COUNTY	ROUTE	POST MILES TOTAL PROJECT	SHEET No.	TOTAL SHEETS
03	Nev, Pla	20,267	0.0/R6.6 6.8/9.9	4	14

Scott W. Mann 4-4-16
 REGISTERED CIVIL ENGINEER DATE
 4-4-16
 PLANS APPROVAL DATE

REGISTERED PROFESSIONAL ENGINEER
SCOTT MANN
 No. 72005
 Exp. 6-30-16
 CIVIL
 STATE OF CALIFORNIA

THE STATE OF CALIFORNIA OR ITS OFFICERS OR AGENTS SHALL NOT BE RESPONSIBLE FOR THE ACCURACY OR COMPLETENESS OF SCANNED COPIES OF THIS PLAN SHEET.



DETAIL 22B
CENTERLINE RUMBLE STRIPS AND STRIPING
AT BRIDGE STRUCTURES

LOCATION 1: SLACKS RAVINE (Br No. 17-0104) (PM 0.96)
 LOCATION 1: SLACKS RAVINE (Br No. 17-0105) (PM 1.37)

STATE OF CALIFORNIA - DEPARTMENT OF TRANSPORTATION
Caltrans
 DESIGN
 FUNCTIONAL SUPERVISOR: SCOTT W. MANN
 CALCULATED/DESIGNED BY: CHRISTOPHER BRADANICK
 CHECKED BY: RODOLFO AVILA
 REVISED BY: DATE REVISED:

CONSTRUCTION DETAILS

NO SCALE

C-3


Dist	COUNTY	ROUTE	POST MILES TOTAL PROJECT	SHEET No.	TOTAL SHEETS
03	NeV,Pla	20,267	0.0/R6.6 6.8/9.9	5	14
 REGISTERED CIVIL ENGINEER			4-4-16 DATE		
4-4-16 PLANS APPROVAL DATE					
<small>THE STATE OF CALIFORNIA OR ITS OFFICERS OR AGENTS SHALL NOT BE RESPONSIBLE FOR THE ACCURACY OR COMPLETENESS OF SCANNED COPIES OF THIS PLAN SHEET.</small>					

NOTE:


AT LOCATION 1, SHOULDER RUMBLE STRIPS SHALL HAVE A 12-FOOT GAP EVERY 60'.

LEGEND


-  DIRECTION OF TRAVEL
-  RUMBLE STRIP (HMA, GROUND-IN INDENTATIONS)




CENTERLINE AND SHOULDER RUMBLE STRIPS AT GRADE INTERSECTION



CENTERLINE AND SHOULDER RUMBLE STRIPS AT BRIDGE APPROACH



CENTERLINE AND SHOULDER RUMBLE STRIPS AT DRIVEWAY/PRIVATE ROAD APPROACH




SHOULDER RUMBLE STRIPS (LOCATION 1)


CONSTRUCTION DETAILS

NO SCALE


C-4

STATE OF CALIFORNIA - DEPARTMENT OF TRANSPORTATION
 Christopher Bradanick
 Rodolfo Avila
 Scott W. Mann
 DESIGN


Dist	COUNTY	ROUTE	POST MILES TOTAL PROJECT	SHEET No.	TOTAL SHEETS
03	Nev, Pla	20,267	0.0/R6.6 6.8/9.9	6	14
 REGISTERED CIVIL ENGINEER			4-4-16	DATE	
PLANS APPROVAL DATE			4-4-16		
<small>THE STATE OF CALIFORNIA OR ITS OFFICERS OR AGENTS SHALL NOT BE RESPONSIBLE FOR THE ACCURACY OR COMPLETENESS OF SCANNED COPIES OF THIS PLAN SHEET.</small>					
					



**CENTERLINE AND SHOULDER RUMBLE STRIPS
AT INTERSECTION WITH LEFT TURN POCKETS**



**CENTERLINE RUMBLE STRIP CONFIGURATION
AT PM 0.07 - 0.58 (LOCATION 1)**



**CENTERLINE AND SHOULDER RUMBLE STRIPS
AT PUBLIC ROAD T-INTERSECTION**

CONSTRUCTION DETAILS

NO SCALE

C-5

STATE OF CALIFORNIA - DEPARTMENT OF TRANSPORTATION
 DESIGN
 FUNCTIONAL SUPERVISOR: SCOTT W. MANN
 CALCULATED/DESIGNED BY: CHRISTOPHER BRADANICK
 CHECKED BY: RODOLFO AVILA
 REVISED BY: DATE REVISIONS
 00-00-00
 00-00-00
 00-00-00

Dist	COUNTY	ROUTE	POST MILES TOTAL PROJECT	SHEET No.	TOTAL SHEETS
03	Nev,Pla	20,267	0.0/R6.6 6.8/9.9	7	14

Scott W. Mann 4-4-16
 REGISTERED CIVIL ENGINEER DATE

4-4-16
 PLANS APPROVAL DATE

THE STATE OF CALIFORNIA OR ITS OFFICERS
 OR AGENTS SHALL NOT BE RESPONSIBLE FOR
 THE ACCURACY OR COMPLETENESS OF SCANNED
 COPIES OF THIS PLAN SHEET.

NOTES:

1. EXACT SIGN LOCATIONS TO BE DETERMINED BY THE ENGINEER.
2. POST MILE LOCATIONS ARE APPROXIMATE.

STATIONARY MOUNTED CONSTRUCTION AREA SIGNS

LOCATION NUMBER	COUNTY AND ROUTE	SIGN LOCATION AND DESCRIPTION	FACING TRAFFIC				SIGN CODE		SIGN MESSAGE	PANEL SIZE	NUMBER AND SIZE OF POST	NUMBER OF SIGNS		
			NB	SB	EB	WB	FEDERAL	CALIFORNIA						
①	Yub-20	500 LF BEFORE THE BEGINNING OF RUMBLE STRIPS - PM 21.57			1		G20-1[Spec](7)		ROAD WORK NEXT 7 MILES	60" x 30"	2-4"x4"	1		
		250 LF BEFORE THE BEGINNING OF RUMBLE STRIPS - PM 21.62				1	G20-2	C14	END ROAD WORK	36" x 18"	1-4"x4"	1		
		PM 21.62			1			C40(Mod)	TRAFFIC FINES DOUBLED IN WORK ZONES	48" x 36"	1-4"x6"	1		
	Nev-20	MOONEY FLAT ROAD - PM 0.09		1			W20-1	C23	ROAD WORK AHEAD	48" x 48"	1-6"x6"	1		
		MELODY ROAD - PM 1.94	1				W20-1	C23	ROAD WORK AHEAD	48" x 48"	1-6"x6"	1		
		PENN VALLEY DRIVE - PM R3.62	1				W20-1	C23	ROAD WORK AHEAD	48" x 48"	1-6"x6"	1		
		PLEASANT VALLEY ROAD - PM R4.65	1	1			W20-1	C23	ROAD WORK AHEAD	48" x 48"	1-6"x6"	2		
		CATTLE DRIVE - PM R6.24		1			W20-1	C23	ROAD WORK AHEAD	48" x 48"	1-6"x6"	1		
		PM R6.5				1		C40(Mod)	TRAFFIC FINES DOUBLED IN WORK ZONES	48" x 36"	1-4"x6"	1		
		ROUGH AND READY HIGHWAY - PM R6.6	1	1			W20-1	C23	ROAD WORK AHEAD	48" x 48"	1-6"x6"	2		
		JUST EAST OF Rte 20/ ROUGH AND READY Hwy INTERSECTION - PM R6.65			1		G20-2	C14	END ROAD WORK	36" x 18"	1-4"x4"	1		
		JUST EAST OF Rte 20/ ROUGH AND READY Hwy INTERSECTION - PM R6.75				1	G20-1[Spec](7)		ROAD WORK NEXT 7 MILES	60" x 30"	2-4"x4"	1		
		②	Pla-267	500 LF BEFORE THE BEGINNING OF RUMBLE STRIPS - PM 6.70		1			G20-1[Spec](3)		ROAD WORK NEXT 3 MILES	60" x 30"	2-4"x4"	1
				250 LF BEFORE THE BEGINNING OF RUMBLE STRIPS - PM 6.75	1				G20-2	C14	END ROAD WORK	36" x 18"	1-4"x4"	1
PM 6.75				1				C40(Mod)	TRAFFIC FINES DOUBLED IN WORK ZONES	48" x 36"	1-4"x6"	1		
N NATIONAL AVENUE - PM 8.39					1		W20-1	C23	ROAD WORK AHEAD	48" x 48"	1-6"x6"	1		
STEWART WAY - PM 8.72					1	1	W20-1	C23	ROAD WORK AHEAD	48" x 48"	1-6"x6"	2		
KINGSWOOD DRIVE - PM 8.93					1	1	W20-1	C23	ROAD WORK AHEAD	48" x 48"	1-6"x6"	2		
LINCOLN GREEN DRIVE/ CAMBRIDGE DRIVE - PM 9.06					1	1	W20-1	C23	ROAD WORK AHEAD	48" x 48"	1-6"x6"	2		
PINEDROP LANE - PM 9.19					1		W20-1	C23	ROAD WORK AHEAD	48" x 48"	1-6"x6"	1		
NORTH AVENUE - PM 9.28					1		W20-1	C23	ROAD WORK AHEAD	48" x 48"	1-6"x6"	1		
TIGER AVENUE - PM 9.35					1		W20-1	C23	ROAD WORK AHEAD	48" x 48"	1-6"x6"	1		
SPECKLED STREET - PM 9.52						1	W20-1	C23	ROAD WORK AHEAD	48" x 48"	1-6"x6"	1		
DOLLY VARDEN AVENUE - PM 9.63						1	W20-1	C23	ROAD WORK AHEAD	48" x 48"	1-6"x6"	1		
PM 9.85	1							C40(Mod)	TRAFFIC FINES DOUBLED IN WORK ZONES	48" x 36"	1-4"x6"	1		
JUST NORTH OF ROUTE 267/ N LAKE Blvd INTERSECTION - PM 9.90				1			G20-2	C14	END ROAD WORK	36" x 18"	1-4"x4"	1		
JUST NORTH OF ROUTE 267/ N LAKE Blvd INTERSECTION - PM 9.90	1				G20-1[Spec](3)		ROAD WORK NEXT 3 MILES	60" x 30"	2-4"x4"	1				

STATE OF CALIFORNIA - DEPARTMENT OF TRANSPORTATION
 DESIGN
 SCOTT W. MANN
 FUNCTIONAL SUPERVISOR
 CHECKED BY
 RODOLFO AVILA
 CHRISTOPHER BRADANICK
 REVISOR BY
 DATE REVISED

**CONSTRUCTION AREA SIGNS
CS-1**

LAST REVISION DATE PLOTTED => 06-APR-2016
 00-00-00 TIME PLOTTED => 11:19



Dist	COUNTY	ROUTE	POST MILES TOTAL PROJECT	SHEET No.	TOTAL SHEETS
03	Nev, Pla	20,267	0.0/R6.6 6.8/9.9	8	14

<i>Scott W. Mann</i> REGISTERED CIVIL ENGINEER	4-4-16 DATE
4-4-16 PLANS APPROVAL DATE	

REGISTERED PROFESSIONAL ENGINEER	SCOTT MANN
No. 72005	Exp. 6-30-16
CIVIL	


THE STATE OF CALIFORNIA OR ITS OFFICERS OR AGENTS SHALL NOT BE RESPONSIBLE FOR THE ACCURACY OR COMPLETENESS OF SCANNED COPIES OF THIS PLAN SHEET.

G20-1(Spec)(7)





3/4" BORDER WITH 2" RADIUS AND 1/2" INDENT
 RETROREFLECTIVE FLUORESCENT ORANGE BACKGROUND
 WITH BLACK LEGEND AND BORDER
 "ROAD WORK" C SERIES LETTERS
 "NEXT 7 MILES" C SERIES LETTERS

C40(Mod) <CA>



3/4" BORDER WITH 2 1/4" RADIUS AND 1/2" INDENT
 RETROREFLECTIVE WHITE BACKGROUND
 WITH BLACK LEGEND AND BORDER
 "TRAFFIC FINES" D SERIES LETTERS
 "DOUBLED IN" D SERIES LETTERS
 "WORK ZONES" D SERIES LETTERS

G20-1(Spec)(3)



3/4" BORDER WITH 2" RADIUS AND 1/2" INDENT
 RETROREFLECTIVE FLUORESCENT ORANGE BACKGROUND
 WITH BLACK LEGEND AND BORDER
 "ROAD WORK" C SERIES LETTERS
 "NEXT 3 MILES" C SERIES LETTERS

STATE OF CALIFORNIA - DEPARTMENT OF TRANSPORTATION	DESIGN
<i>Caltrans</i>	
FUNCTIONAL SUPERVISOR	SCOTT W. MANN
CALCULATED/DESIGNED BY	CHECKED BY
CHRISTOPHER BRADANICK	RODOLFO AVILA
REVISED BY	DATE

APPROVED FOR CONSTRUCTION AREA SIGN WORK ONLY

CONSTRUCTION AREA SIGNS
 NO SCALE
CS-2

LAST REVISION DATE PLOTTED => 06-APR-2016
 00-00-00 TIME PLOTTED => 11:19

Dist	COUNTY	ROUTE	POST MILES TOTAL PROJECT	SHEET No.	TOTAL SHEETS
03	Nev,Pla	20,267	0.0/R6.6 6.8/9.9	9	14

Scott W. Mann 4-4-16
 REGISTERED CIVIL ENGINEER DATE

4-4-16
 PLANS APPROVAL DATE

THE STATE OF CALIFORNIA OR ITS OFFICERS
 OR AGENTS SHALL NOT BE RESPONSIBLE FOR
 THE ACCURACY OR COMPLETENESS OF SCANNED
 COPIES OF THIS PLAN SHEET.

NOTES:

1. POST MILE LOCATIONS ARE APPROXIMATE.
2. PAVEMENT DELINEATION SHALL MATCH EXISTING.
3. EWNV = ENHANCED WET NIGHT VISIBILITY.

THERMOPLASTIC TRAFFIC STRIPE AND PAVEMENT MARKERS

No.	COUNTY	ROUTE	PM TO PM	REMOVE THERMOPLASTIC TRAFFIC STRIPE LF	REMOVE PAVEMENT MARKER * EA	4" THERMOPLASTIC TRAFFIC STRIPE (EWNV)				4" THERMOPLASTIC TRAFFIC STRIPE (EWNV)		4" THERMOPLASTIC TRAFFIC STRIPE (EWNV)		4" TWO-COMPONENT PAINT TRAFFIC STRIPE		4" TWO-COMPONENT PAINT TRAFFIC STRIPE		PAVEMENT MARKER (RETROREFLECTIVE)		PAVEMENT MARKER (NON-REFLECTIVE)
						DETAIL No.				DETAIL No.		DETAIL No.		DETAIL No.		TYPE D	TYPE H	TYPE A		
						19 LF	22 LF	22B LF	27B LF	27C LF	6 LF	19 LF	18 LF	21 LF	5 LF	18 LF	YELLOW EA	YELLOW EA	BLACK EA	
①	Nev	20	0.0 TO R6.6	66,547	2,614	4,436	53,313	824	67,613	744	3,538	4,436					2,428	186	174	
②	Pla	267	6.8 TO 9.9	67,094									1,320	30,664	687	1,320				
SUBTOTAL				133,641	2,614	4,436	53,313	824	67,613	744	3,538	4,436	1,320	30,664	687	1,320	2,428	186	174	
TOTAL				133,641	2,614	126,186				744	7,974		31,984		2,007		2,614		174	

* PAID FOR AS LUMP SUM

SUMMARY OF QUANTITIES

Q-1

STATE OF CALIFORNIA - DEPARTMENT OF TRANSPORTATION

 DESIGN
 FUNCTIONAL SUPERVISOR: SCOTT W. MANN
 CALCULATED/DESIGNED BY: CHRISTOPHER BRADANICK
 CHECKED BY: RODOLFO AVILA
 REVISED BY: DATE REVISED:

RUMBLE STRIPS

LOCATION				CENTERLINE RUMBLE STRIP (HMA, GROUND-IN INDENTATIONS)	SHOULDER RUMBLE STRIP (HMA, GROUND-IN INDENTATIONS)	ASPHALTIC EMULSION (FOG SEAL COAT)
No.	COUNTY	ROUTE	PM TO PM	STA	STA	TON
①	Nev	20	0.0 TO R6.6	347	412	13
②	Pla	267	6.8 TO 9.9	139		3
TOTAL				486	412	16

TEMPORARY DRAINAGE INLET PROTECTION

LOCATION				TEMPORARY DRAINAGE INLET PROTECTION
No.	COUNTY	ROUTE	PM TO PM	EA
①	Nev	20	0.0 TO R6.6	9
②	Pla	267	6.8 TO 9.9	87
TOTAL				96

Dist	COUNTY	ROUTE	POST MILES TOTAL PROJECT	SHEET No.	TOTAL SHEETS
03	Nev, Pla	20, 267	0.0/R6.6 6.8/9.9	10	14

Scott W. Mann 4-4-16
 REGISTERED CIVIL ENGINEER DATE

4-4-16
 PLANS APPROVAL DATE

THE STATE OF CALIFORNIA OR ITS OFFICERS
 OR AGENTS SHALL NOT BE RESPONSIBLE FOR
 THE ACCURACY OR COMPLETENESS OF SCANNED
 COPIES OF THIS PLAN SHEET.

SUMMARY OF QUANTITIES

	M	
Maint	MAINTENANCE	
Max	MAXIMUM	
MB	METAL BEAM	
MBB	METAL BEAM BARRIER	
MBGR	METAL BEAM GUARD RAILING	
Med	MEDIAN	
MGS	MIDWEST GUARDRAIL SYSTEM	
MH	MANHOLE	
Min	MINIMUM	
Misc	MISCELLANEOUS	
Misc I & S	MISCELLANEOUS IRON AND STEEL	
Mkr	MARKER	
Mod	MODIFIED, MODIFY	
Mon	MONUMENT	
MP	METAL PLATE	
MPGR	METAL PLATE GUARD RAILING	
MR	MOVEMENT RATING	
MSE	MECHANICALLY STABILIZED EMBANKMENT	
Mt	MOUNTAIN, MOUNT	
MtI	MATERIAL	
MVP	MAINTENANCE VEHICLE PULLOUT	
	N	
N	NORTH	
NB	NORTHBOUND	
No.	NUMBER (MUST HAVE PERIOD)	
Nos.	NUMBERS (MUST HAVE PERIOD)	
NPS	NOMINAL PIPE SIZE	
NS	NEAR SIDE	
NSP	NEW STANDARD PLAN	
NTS	NOT TO SCALE	
	O	
Obir	OBLITERATE	
OC	OVERCROSSING	
OD	OUTSIDE DIAMETER	
OF	OUTSIDE FACE	
OG	ORIGINAL GROUND	
OGAC	OPEN GRADED ASPHALT CONCRETE	
OGFC	OPEN GRADED FRICTION COURSE	
OH	OVERHEAD	
OHWM	ORDINARY HIGH WATER MARK	
O-O	OUT TO OUT	
Opp	OPPOSITE	
OSD	OVERSIDE DRAIN	
	P	
p	PAGE	
PAP	PERFORATED ALUMINUM PIPE	
PB	PULL BOX	
PC	POINT OF CURVATURE, PRECAST	
PCC	POINT OF COMPOUND CURVE, PORTLAND CEMENT CONCRETE	
PCMS	PORTABLE CHANGEABLE MESSAGE SIGN	
PCP	PERFORATED CONCRETE PIPE, PRESTRESSED CONCRETE PIPE	
PCVC	POINT OF COMPOUND VERTICAL CURVE	
PEC	PERMIT TO ENTER AND CONSTRUCT	
Ped	PEDESTRIAN	
Ped OC	PEDESTRIAN OVERCROSSING	
Ped UC	PEDESTRIAN UNDERCROSSING	
Perm MtI	PERMEABLE MATERIAL	

	P continued	
PG	PROFILE GRADE	
PI	POINT OF INTERSECTION	
PJP	PARTIAL JOINT PENETRATION	
Pkwy	PARKWAY	
PL, PL	PLATE	
P/L	PROPERTY LINE	
PM	POST MILE, TIME FROM NOON TO MIDNIGHT	
PN	PAVING NOTCH	
POC	POINT OF HORIZONTAL CURVE	
POT	POINT OF TANGENT	
POVC	POINT OF VERTICAL CURVE	
PP	PIPE PILE, PLASTIC PIPE, POWER POLE	
PPL	PREFORMED PERMEABLE LINER	
PPP	PERFORATED PLASTIC PIPE	
PRC	POINT OF REVERSE CURVE	
PRF	PAVEMENT REINFORCING FABRIC	
PRVC	POINT OF REVERSE VERTICAL CURVE	
PS&E	PLANS, SPECIFICATIONS AND ESTIMATES	
PS, P/S	PRESTRESSED	
PSP	PERFORATED STEEL PIPE	
PT	POINT OF TANGENCY	
PVC	POLYVINYL CHLORIDE	
Pvmt	PAVEMENT	
	Q	
Qty	QUANTITY	
	R	
R	RADIUS	
R & D	REMOVE AND DISPOSE	
R & S	REMOVE AND SALVAGE	
R/C	RATE OF CHANGE	
RCA	REINFORCED CONCRETE ARCH	
RCB	REINFORCED CONCRETE BOX	
RCP	REINFORCED CONCRETE PIPE	
RCPA	REINFORCED CONCRETE PIPE ARCH	
Rd	ROAD	
Reinf	REINFORCED, REINFORCEMENT, REINFORCING	
Rel	RELOCATE	
Repl	REPLACEMENT	
Ret	RETAINING	
Rev	REVISED, REVISION	
Rdwy	ROADWAY	
RHMA	RUBBERIZED HOT MIX ASPHALT	
Riv	RIVER	
RM	ROAD-MIXED	
RP	RADIUS POINT, REFERENCE POINT	
RR	RAILROAD	
RSP	ROCK SLOPE PROTECTION, REVISED STANDARD PLAN	
Rt	RIGHT	
Rte	ROUTE	
RW	REDWOOD, RETAINING WALL	
R/W	RIGHT OF WAY	
Rwy	RAILWAY	

	S	
S	SOUTH, SUPPLEMENT	
SAE	STRUCTURE APPROACH EMBANKMENT	
Salv	SALVAGE	
SAPP	STRUCTURAL ALUMINUM PLATE PIPE	
SB	SOUTHBOUND	
SC	SAND CUSHION	
SCSP	SLOTTED CORRUGATED STEEL PIPE	
SD	STORM DRAIN	
Sec	SECOND, SECTION	
Sep	SEPARATION	
SG	SUBGRADE	
Shld	SHOULDER	
Sht	SHEET	
Sim	SIMILAR	
SL	STATION LINE	
SM	SELECTED MATERIAL	
Spec	SPECIAL, SPECIFICATIONS	
SPP	SLOTTED PLASTIC PIPE	
SS	SLOPE STAKE	
SSBM	STRAP AND SADDLE BRACKET METHOD	
SSD	STRUCTURAL SECTION DRAIN	
SSPA	STRUCTURAL STEEL PLATE ARCH	
SSPP	STRUCTURAL STEEL PLATE PIPE	
SSPPA	STRUCTURAL STEEL PLATE PIPE ARCH	
SSRP	STEEL SPIRAL RIB PIPE	
St	STREET	
Sta	STATION	
STBB	SINGLE THRIE BEAM BARRIER	
Std	STANDARD	
Str	STRUCTURE	
Surf	SURFACING	
SW	SIDEWALK, SOUND WALL	
Swr	SEWER	
Sym	SYMMETRICAL	
S4S	SURFACE 4 SIDES	
	T	
T	SEMI-TANGENT	
Tan	TANGENT	
TBB	THRIE BEAM BARRIER	
Tbr	TIMBER	
TC	TOP OF CURB	
TCB	TRAFFIC CONTROL BOX	
TCE	TEMPORARY CONSTRUCTION EASEMENT	
TeI	TELEPHONE	
Temp	TEMPORARY	
TG	TOP OF GRADE	
Tot	TOTAL	
TP	TELEPHONE POLE	
TPB	TREATED PERMEABLE BASE	
TPM	TREATED PERMEABLE MATERIAL	
Trans	TRANSITION	

	T continued	
TS	TRANSVERSE, TRAFFIC SIGNAL, TUBULAR STEEL	
Typ	TYPICAL	U
UC	UNDERCROSSING	
UD	UNDERDRAIN	
UG	UNDERGROUND	
UON	UNLESS OTHERWISE NOTED	
UP	UNDERPASS	V
V	VALVE, DESIGN SPEED	
Var	VARIABLE, VARIES	
VC	VERTICAL CURVE	
VCP	VITRIFIED CLAY PIPE	
Vert	VERTICAL	
Via	VIADUCT	
Vol	VOLUME	W
W	WEST, WIDTH	
WB	WESTBOUND	
WH	WEEP HOLE	
WM	WIRE MESH	
WS	WATER SURFACE	
WSP	WELDED STEEL PIPE	
Wt	WEIGHT	
WV	WATER VALVE	
WW	WINGWALL	
WWL	WINGWALL LAYOUT LINE	X
X Sec	CROSS SECTION	
Xing	CROSSING	Y
Yr	YEAR	
Yrs	YEARS	

Dist	COUNTY	ROUTE	POST MILES TOTAL PROJECT	SHEET No.	TOTAL SHEETS
03	Nev, Pla	20,267	0.0/R6.6, 6.8/9.9'	11	14

Grace M. Tsushima
REGISTERED CIVIL ENGINEER

July 19, 2013
PLANS APPROVAL DATE

REGISTERED PROFESSIONAL ENGINEER
 Grace M. Tsushima
 No. C49814
 Exp. 9-30-14
 CIVIL
 STATE OF CALIFORNIA

THE STATE OF CALIFORNIA OR ITS OFFICERS OR AGENTS SHALL NOT BE RESPONSIBLE FOR THE ACCURACY OR COMPLETENESS OF SCANNED COPIES OF THIS PLAN SHEET.

TO ACCOMPANY PLANS DATED 4-4-16

UNIT OF MEASUREMENT SYMBOLS:
Some of the symbols used in the project plan quantity tables and in the Bid Item List are:

TABLE A

SYMBOL USED	DEFINITIONS
ACRE	ACRE
CF	CUBIC FOOT
CY	CUBIC YARD
EA	EACH
GAL	GALLON
LB	POUND
LF	LINEAR FOOT
SQFT	SQUARE FOOT
SQYD	SQUARE YARD
STA	100 FEET
TAB	TABLET
TON	2,000 POUNDS

Some of the symbols used in the plans other than in the project plan quantity tables are:

TABLE B

SYMBOL USED	DEFINITIONS
ksi	KIPS PER SQUARE INCH
ksf	KIPS PER SQUARE FOOT
psi	POUNDS PER SQUARE INCH
psf	POUNDS PER SQUARE FOOT
lb/ft ³ , pcf	POUNDS PER CUBIC FOOT
tsf	TONS PER SQUARE FOOT
mph, MPH *	MILES PER HOUR
ø	NOMINAL DIAMETER
oz	OUNCE
lb	POUND
kíp	1,000 POUNDS
cal	CALORIE
ft	FOOT OR FEET
gal	GALLON

* For use on a sign panel only

STATE OF CALIFORNIA
DEPARTMENT OF TRANSPORTATION

**ABBREVIATIONS
(SHEET 2 OF 2)**

NO SCALE

RSP A10B DATED JULY 19, 2013 SUPERSEDES STANDARD PLAN A10B
DATED MAY 20, 2011 - PAGE 2 OF THE STANDARD PLANS BOOK DATED 2010.

2010 REVISED STANDARD PLAN RSP A10B

TO ACCOMPANY PLANS DATED 4-4-16

TABLE 1

TAPER LENGTH CRITERIA AND CHANNELIZING DEVICE SPACING							
SPEED (S)	MINIMUM TAPER LENGTH * FOR WIDTH OF OFFSET 12 FEET (W)				MAXIMUM CHANNELIZING DEVICE SPACING		
	TANGENT 2L	MERGING L	SHIFTING L/2	SHOULDER L/3	X	Y	Z **
					TAPER	TANGENT	CONFLICT
mph	ft	ft	ft	ft	ft	ft	ft
20	160	80	40	27	20	40	10
25	250	125	63	42	25	50	12
30	360	180	90	60	30	60	15
35	490	245	123	82	35	70	17
40	640	320	160	107	40	80	20
45	1080	540	270	180	45	90	22
50	1200	600	300	200	50	100	25
55	1320	660	330	220	55	110	27
60	1440	720	360	240	60	120	30
65	1560	780	390	260	65	130	32
70	1680	840	420	280	70	140	35

* - For other offsets, use the following merging taper length formula for L:
 For speed of 40 mph or less, $L = WS^2/60$
 For speed of 45 mph or more, $L = WS$

Where: L = Taper length in feet
 W = Width of offset in feet
 S = Posted speed limit, off-peak 85th-percentile speed prior to work starting, or the anticipated operating speed in mph

** - Use for taper and tangent sections where there are no pavement markings or where there is a conflict between existing pavement markings and channelizers (CA).

TABLE 2

LONGITUDINAL BUFFER SPACE AND FLAGGER STATION SPACING				
SPEED *	Min D **	DOWNGRADE Min D ***		
		-3%	-6%	-9%
		ft	ft	ft
mph	ft	ft	ft	ft
20	115	116	120	126
25	155	158	165	173
30	200	205	215	227
35	250	257	271	287
40	305	315	333	354
45	360	378	400	427
50	425	446	474	507
55	495	520	553	593
60	570	598	638	686
65	645	682	728	785
70	730	771	825	891

* - Speed is posted speed limit, off-peak 85th-percentile speed prior to work starting, or the anticipated operating speed in mph
 ** - Longitudinal buffer space or flagger station spacing
 *** - Use on sustained downgrade steeper than -3 percent and longer than 1 mile.

TABLE 3

ADVANCE WARNING SIGN SPACING			
ROAD TYPE	DISTANCE BETWEEN SIGNS *		
	A	B	C
	ft	ft	ft
URBAN - 25 mph OR LESS	100	100	100
URBAN - MORE THAN 25 mph TO 40 mph	250	250	250
URBAN - MORE THAN 40 mph	350	350	350
RURAL	500	500	500
EXPRESSWAY / FREEWAY	1000	1500	2640

* - The distances are approximate, are intended for guidance purposes only, and should be applied with engineering judgment. These distances should be adjusted by the Engineer for field conditions, if necessary, by increasing or decreasing the recommended distances.

STATE OF CALIFORNIA
 DEPARTMENT OF TRANSPORTATION

TRAFFIC CONTROL SYSTEM TABLES FOR LANE AND RAMP CLOSURES

NO SCALE

RSP T9 DATED JULY 19, 2013 SUPERSEDES RSP T9 DATED APRIL 19, 2013 THAT SUPPLEMENTS THE STANDARD PLANS BOOK DATED 2010.

2010 REVISED STANDARD PLAN RSP T9

Dist	COUNTY	ROUTE	POST MILES TOTAL PROJECT	SHEET No.	TOTAL SHEETS
03	Nev, Pla	20,267	0.0/R6.6, 6.8/9.9'	13	14

Devinder Singh
 REGISTERED CIVIL ENGINEER
 No. C50470
 Exp. 6-30-17
 CIVIL
 STATE OF CALIFORNIA

October 30, 2015
 PLANS APPROVAL DATE

THE STATE OF CALIFORNIA OR ITS OFFICERS
 OR AGENTS SHALL NOT BE RESPONSIBLE FOR
 THE ACCURACY OR COMPLETENESS OF SCANNED
 COPIES OF THIS PLAN SHEET.

NOTES:

See Revised Standard Plan RSP T9 for tables.


Use cone spacing X for taper segment, Y for tangent segment or Z for conflict situations, as appropriate, per Table 1, unless X, Y, or Z cone spacing is shown on this sheet.

Unless otherwise specified in the special provisions, all temporary warning signs shall have black legend on fluorescent orange background.

California codes are designated by (CA). Otherwise, Federal (MUTCD) codes are shown.


TYPICAL LANE CLOSURE WITH REVERSIBLE CONTROL

TO ACCOMPANY PLANS DATED 4-4-16



- NOTES:**
- Each advance warning sign in each direction of travel shall be equipped with at least two flags for daytime closure. Each flag shall be at least 16" x 16" in size and shall be orange or fluorescent red-orange in color. Flashing beacons shall be placed at the locations indicated for lane closure during hours of darkness.
 - A G20-2 "END ROAD WORK" sign, as appropriate, shall be placed at the end of the lane control unless the end of work area is obvious, or ends within a larger project's limits.
 - If the W20-1 sign would follow within 2000' of a stationary W20-1 or G20-1 "ROAD WORK NEXT _____ MILES", use a W20-4 sign for the first advance warning sign.
 - All cones used for lane closures during the hours of darkness shall be fitted with retroreflective bands (or sleeves) as specified in the specifications.
 - Portable delineators, placed at one-half the spacing indicated for traffic cones, may be used instead of cones for daytime closures only.
 - Additional advance flaggers may be required. Flagger should stand in a conspicuous place, be visible to approaching traffic as well as approaching vehicles after the first vehicle has stopped. During the hours of darkness, the flagging-station and flagger shall be illuminated and clearly visible to approaching traffic. The illumination footprint of the lighting on the ground shall be at least 20' in diameter. Place a minimum of four cones at 50' intervals in advance of flagger station as shown.

- Place C30(CA) "LANE CLOSED" sign at 500' to 1000' intervals throughout extended work areas. They are optional if the work area is visible from the flagger station.
- When a pilot car is used, place a C37(CA) "TRAFFIC CONTROL-WAIT AND FOLLOW PILOT CAR" sign with black legend on white background at all intersections, driveways and alleys without a flagger within traffic control area. Signs shall be clean and visible at all times. Where traffic can not be effectively self-regulated, at least one flagger shall be used at each intersection within traffic control area.
- An optional C29(CA) sign may be placed below the C9A(CA) sign.
- Either traffic cones or barricades shall be placed on the taper. Barricades shall be Type I, II, or III.
- The color of the portable transverse rumble strips shall be black or orange. Use 2 arrays, each array shall consist of 3 rumble strips.
- Portable transverse rumble strips shall not be placed on sharp horizontal or vertical curves nor shall they be placed through pedestrian crossings.
- If the portable transverse rumble strips become out of alignment (skewed) by more than 6 inches, measured from one end to the other, they shall be readjusted to bring the placement back to the original location.
- Portable transverse rumble strips are not required if any one of the following conditions is satisfied:
 - Work duration occupies a location for four hours or less
 - Posted speed limit is below 45 MPH
 - Work is of emergency nature
 - Work zone is in snow or icy weather conditions



SIGN PANEL SIZE (Min)

- A 48" x 48"
- B 30" x 30"
- C 36" x 18"
- D 36" x 42"
- E 20" x 7"

LEGEND

- TRAFFIC CONE
- ⊥ TEMPORARY TRAFFIC CONTROL SIGN
- ⚡ PORTABLE FLASHING BEACON
- 🚧 FLAGGER


STATE OF CALIFORNIA
 DEPARTMENT OF TRANSPORTATION
**TRAFFIC CONTROL SYSTEM
 FOR LANE CLOSURE ON
 TWO LANE CONVENTIONAL
 HIGHWAYS**
 NO SCALE

RSP T13 DATED OCTOBER 30, 2015 SUPERSEDES
 RSP T13 DATED OCTOBER 17, 2014, RSP T13 DATED JULY 18, 2014
 AND RSP T13 DATED APRIL 19, 2013 AND STANDARD PLAN T13 DATED
 MAY 20, 2011 - PAGE 241 OF THE STANDARD PLANS BOOK DATED 2010.

REVISED STANDARD PLAN RSP T13

2010 REVISED STANDARD PLAN RSP T13

TO ACCOMPANY PLANS DATED 4-4-16



NOTES:

1. Either a changeable message sign or a SC12(CA) "SLOW TRAFFIC AHEAD" sign shall be mounted on the rear of sign vehicle V1. The changeable message sign shall be sequenced to show the "CAUTION" message first, follow by the "SLOW TRAFFIC AHEAD" message. A Type II flashing arrow sign may be used with the SC12(CA) sign panel.
2. Sign vehicle V1 should be positioned where highly visible when shoulders are not available.
3. If traffic queues develop, sign vehicle V1 should be positioned upstream from the end of queue.
4. Vehicle-mounted sign panels shall have Type III or above retroreflective sheeting, black on white, or black on fluorescent orange, with 6" minimum series D letters per Caltrans sign specifications.
5. Shadow vehicle shall be equipped with a truck-mounted attenuator. The sign panel shown shall be mounted on the rear of shadow vehicle V2. The message "LANE CLOSED" may be used in place of the "DO NOT PASS" message.
6. The sign panel shown shall be mounted on the front of sign vehicle V4, facing opposing traffic.

7. All vehicles shall be equipped with flashing or rotating amber lights.
8. Sign vehicle V4 will not be required when the work and vehicles V2 and V3 are 2' or more from the centerline of the highway during the work or application operations.
9. All vehicles used for lane closures shall be equipped with two-way radios and the vehicle operators shall maintain communication during the work or application operation.
10. This plan shall not be used where workers would be on foot in the work area. Use a stationary type lane closure (Revised Standard Plan T13) for this condition.
11. Minimize spacing between vehicles V2 and V3 and vehicles V3 and V4 to deter road users from driving in between them.
12. If sign vehicle V1 encroaches into the traffic lane due to insufficient shoulder width, sign vehicle V1 shall be equipped with a truck-mounted attenuator. Sign vehicle V1 shall stay as close to the edge of shoulder as practicable.

LEGEND

- V1 SIGN VEHICLE
- V2 SHADOW VEHICLE
- V3 WORK/APPLICATION VEHICLE
- V4 SIGN VEHICLE
- TMA TRUCK-MOUNTED ATTENUATOR
- FLASHING ARROW SIGN (FAS) IN FLASHING CAUTION MODE
- FLASHING ARROW SIGN (FAS) IN ALTERNATING DIAMOND CAUTION

SIGN PANEL SIZE (Min)

- A 72" x 42"
- B 54" x 42"
- C 54" x 24"

STATE OF CALIFORNIA
 DEPARTMENT OF TRANSPORTATION
**TRAFFIC CONTROL SYSTEM
 FOR MOVING LANE CLOSURE
 ON TWO LANE HIGHWAYS**
 NO SCALE

RSP T17 DATED APRIL 19, 2013 SUPERSEDES STANDARD PLAN T17
 DATED MAY 20, 2011 - PAGE 245 OF THE STANDARD PLANS BOOK DATED 2010.

REVISED STANDARD PLAN RSP T17

2010 REVISED STANDARD PLAN RSP T17