

PROFILE



PLAN

GRATE INLET SERIES



DETAIL OF INLET WITH DIKE

(Single grate shown)



PLAN

TYPE GO AND G1 THRU G6 INLETS ON GRADE



PLAN

TYPE OS AND OL INLETS IN SERIES ON GRADE



DETAIL OF HOT MIX ASPHALT PAVEMENT

(See Note 4)

NOTES:

1. W= Width of depressed apron. Depressed aprons shall be 4'-0" on shoulder and 4'-0" to 6'-0" in city street gutters unless otherwise shown.

   D= Gutter depression. The gutter depression shall be 1¼" for shoulder and 1¼" to 3" in city street gutter or locations outside of shoulder unless otherwise shown.

   CH= Curb Height.

   → = Straight grade, downward slope.

   ⇝ = Gutter or shoulders direction of flow.

2. Gutter depressions shall be 8" thick.
3. Establish curb opening height at midpoint of grate.
4. Details shown for concrete pavement. When hot mix asphalt pavement is used, corners to be cut off as shown on Detail of Hot Mix Asphalt Pavement.



PLAN

TYPE GOL INLET ON GRADE



PLAN

TYPE OS AND OL INLETS ON GRADE



SECTION B-B



SECTION C-C



SECTION E-E



SECTION G-G



SECTION D-D



SECTION F-F



SECTION H-H



PLAN

TYPE GO AND GDO INLET GRADE SAG

(GDO shown)



PLAN

TYPE G1 THRU G6 GT3 AND GT4 INLETS IN GRADE SAG



PLAN

TYPE OS AND OL INLETS IN GRADE SAG

Dist	COUNTY	ROUTE	POST MILES TOTAL PROJECT	SHEET No.	TOTAL SHEETS

REGISTERED CIVIL ENGINEER

October 30, 2015

PLANS APPROVAL DATE

REGISTERED PROFESSIONAL ENGINEER Bruce D. Swanger No. C61257 Exp. 6-30-17 CIVIL STATE OF CALIFORNIA

THE STATE OF CALIFORNIA OR ITS OFFICERS OR AGENTS SHALL NOT BE RESPONSIBLE FOR THE ACCURACY OR COMPLETENESS OF SCANNED COPIES OF THIS PLAN SHEET.

STATE OF CALIFORNIA
DEPARTMENT OF TRANSPORTATION

GUTTER DEPRESSIONS

NO SCALE

D78A

2015 STANDARD PLAN D78A

9-22-15